## NSN 5950-00-853-0699

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-853-0699

Thread Class (non-core):

2a single group

Thread Direction (non-core):

Right-hand single group

**Reliability Indicator:** 

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

3.688 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

**Winding Shielding Method:** 

Internal shield grounded to core and brought out to terminal single component

**Body Length:** 

4.688 inches

**Body Width:** 

4.000 inches

**Body Height:** 

6.000 inches

**Inclosure Type:** 

Hermetically sealed

**Mounting Facility Quantity:** 

4 single group

**Mounting Method:** 

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

40 single group

**Thread Size:** 

0.250 inches single group

**Winding Operating Current:** 

490.0 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:** 

55.00 ac pounds per hour wet single component 1st secondary

**Thread Series Designator:** 

Uns single group

**Terminal Type And Quantity:** 

8 solder stud

## NSN 5950-00-853-0699

Power Transformer - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0