

View Online at <https://aerobasegroup.com/nsn/5950-00-854-2156>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.969 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

1.175 inches

Body Width:

1.050 inches

Body Height:

1.250 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

56 single group

Thread Size:

0.086 inches single group

Winding Operating Current:

2.5 milliamperes dc single component 3rd secondary

Winding Operating Voltage:

26.00 ac pounds per hour wet single component single primary

Special Features:

Case metal material; shield w/one solder stud type terminal

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0