NSN 5950-00-854-6833

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-854-6833

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.380 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility single center group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length:
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.380 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility single center group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component
 1.380 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility single center group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component
Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility single center group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component
 1.250 inches single mounting facility single center group Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component
Frequency Rating: 400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component
400.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component
Input-output Phase Relationship: Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component
Single phase to single phase single component Winding Shielding Method: Internal shield grounded to inclosure single component
Winding Shielding Method: Internal shield grounded to inclosure single component
Internal shield grounded to inclosure single component
Body Length:
1.940 inches
Body Width:
1.810 inches
Body Height:
4.000 inches
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded stud single group
Winding Function And Quantity:
1 primary single component and 4 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
2.0 amperes ac single component 1st secondary
Winding Operating Voltage:
44.00 ac volts single component 4th secondary
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
15 wire hook
Shelf Life:
N/a
Unit Of Measure:

NSN 5950-00-854-6833

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

