

View Online at <https://aerobasegroup.com/nsn/5950-00-854-7146>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.390 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.109 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

1.875 inches

Body Width:

1.750 inches

Body Height:

2.375 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.125 inches single group

Winding Operating Current:

30.0 milliamperes ac single component single secondary and 80.0 milliamperes ac single component single secondary

Winding Operating Voltage:

270.00 ac volts single component single secondary and 410.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0