NSN 5950-00-856-1300

Pulse Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-856-1300

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.316 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.688 inches single mounting facility single center group |
| Primary To Secondary Turn Ratio: |
| 100 to 1 single component |
| Pulse Repetition Rate: |
| 225.0 hertz single component |
| Body Length: |
| 4.312 inches |
| Body Width: |
| 3.687 inches |
| Body Height: |
| 4.500 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Current: |
| 1.0 amperes ac single component single secondary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 4 standoff insulator |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

Fiig:

A058b0