NSN 5950-00-856-3068

Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-856-3068

| view Offiline at https://acrobasegroup.com/nsn/3330-00-030-3000 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.312 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.688 inches single mounting facility single center group |
| Impedance Rating In Ohms: |
| 4500.0 single component single primary |
| Frequency Rating: |
| 12.0 kilohertz single component and 14.0 kilohertz single component |
| Maximum Transformer Power Rating: |
| 2300.0 watts single component |
| Primary To Secondary Turn Ratio: |
| 1 to 11-7/10 single component |
| Body Length: |
| 4.375 inches |
| Body Width: |
| 3.750 inches |
| Body Height: |
| 5.562 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.190 inches single group |
| Winding Operating Current: |
| 700.0 milliamperes dc single component single primary |
| Thread Series Designator: |
| Unf single group |
| Terminal Type And Quantity: |
| 4 wire lead |
| Shelf Life: |

--

N/a

Unit Of Measure:

NSN 5950-00-856-3068

Audio Frequency Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0