

View Online at <https://aerobasegroup.com/nsn/5950-00-856-3196>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.812 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.375 inches

Body Width:

2.625 inches

Body Height:

2.812 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary, fixed autotransformer type single component

Winding Tap Location (non-core):

Multiple taps w/center tap single component single primary output

Winding Operating Current:

3.0 amperes ac single component single primary output

Winding Operating Voltage:

16.40 ac pounds per hour wet single component single primary output and 32.80 ac pounds per hour wet single component single primary output and 65.60 ac pounds per hour wet single component single primary output and 82.00 ac pounds per hour wet single component single primary output and 98.40 ac pounds per hour wet single component single primary output

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0