## NSN 5950-00-856-5314

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-856-5314

## Reliability Indicator:

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.625 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.125 inches single mounting facility single center group

#### **Overall Height:**

5.240 inches

#### **Frequency Rating:**

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

#### **Body Length:**

3.560 inches

#### **Body Width:**

3.060 inches

#### **Body Height:**

4.880 inches

## **Maximum Operating Temp:**

65.0 degrees celsius

#### **Inclosure Type:**

Hermetically sealed

#### **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded stud single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### **Thread Size:**

0.164 inches single group

#### **Winding Operating Current:**

3.0 amperes ac single component single secondary

#### **Winding Operating Voltage:**

24.00 ac volts single component single primary and 25.00 ac volts single component single primary and 28.00 ac volts single component single primary and 120.00 ac volts single component single primary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

7 tab, solder lug

#### Shelf Life:

N/a

# **NSN 5950-00-856-5314**Power Transformer - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

Demilitarization:

No

Fiig:

A058b0