

View Online at <https://aerobasegroup.com/nsn/5950-00-856-7042>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

1.875 inches

Body Width:

1.750 inches

Body Height:

2.438 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

150.0 milliamperes ac single component all secondary

Winding Operating Voltage:

6.30 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0