## NSN 5950-00-857-1957

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-857-1957

Polishility Indicators
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.312 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.500 inches single mounting facility single center group
Mounting Hole Diameter:
0.252 inches single group
Inductance Type:
Swinging
Inductance Rating:
5.00 millihenries single component single winding and 50.00 millihenries single component single winding
Body Length:
4.863 inches
Body Width:
3.500 inches
Body Height:
4.620 inches
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and unthreaded hole single group
Winding Operating Current:
750.0 milliamperes dc single component single winding and 7.5 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.180 single component single winding
Terminal Type And Quantity:
2 tab, solder lug
Reference Number Differentiating Characteristics:
As differentiated by navord od 41152
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A058b0