

View Online at <https://aerobasegroup.com/nsn/5950-00-860-0800>

Reliability Indicator:

Not established

Transformer Function:

Line

Impedance Rating In Ohms:

10000.0 single component single secondary

Frequency Rating:

375.0 hertz single component and 150.0 kilohertz single component

Maximum Transformer Power Rating:

50.0 milliwatts single component

Primary To Secondary Turn Ratio:

1 to 1 single component

Body Length:

0.410 inches

Body Width:

0.310 inches

Body Height:

0.475 inches

Maximum Operating Temp:

130.0 degrees celsius

End Application:

Test consoles, mini-sace, support equipment, mx peacekeeper missile, ticonderoga class cg (47), forrestal class cv, missile, air-to-air, sparrow (aim-7), aircraft, c-2a (reprocured), tarawa class lha, emory s. Land class as, arleigh burke class ddg, kidd class ddg

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.0 milliamperes dc single component single primary

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Test Data Document:

07690-417137 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0