

View Online at <https://aerobasegroup.com/nsn/5950-00-860-0808>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

Between 0.558 inches and 0.562 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.398 inches single mounting facility single center group and 0.402 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.398 inches single mounting facility single center group and 0.402 inches single mounting facility single center group

Overall Width:

Between 0.558 inches and 0.562 inches

Primary To Secondary Turn Ratio:

12 to 1 to 6 to 6 single component

Pulse Repetition Rate:

300.0 hertz single component

Body Height:

Between 0.500 inches and 0.520 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component and 2 tertiary single component

Winding Operating Voltage:

6.36 ac volts single component single primary

Test Data Document:

87557-85101 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0