

View Online at <https://aerobasegroup.com/nsn/5950-00-860-7975>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.438 inches single mounting facility single center group

Frequency Rating:

54.0 hertz single component and 66.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.312 inches

Body Width:

2.062 inches

Body Height:

2.500 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

3.0 amperes ac single component single secondary

Winding Power Rating:

15.0 volts-amperes single component single secondary

Winding Operating Voltage:

5.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0