

View Online at <https://aerobasegroup.com/nsn/5950-00-865-5017>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

9.120 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.612 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Three phase to three phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

10.500 inches

**Body Width:**

7.500 inches

**Body Height:**

4.750 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

8 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 4 secondary single component

**Thready Qty Per Inch (tpi):**

18 single group

**Thread Size:**

0.312 inches single group

**Winding Operating Current:**

4.16 amperes ac single component all secondary

**Winding Operating Voltage:**

26.60 ac volts single component 4th secondary

**Special Features:**

Primary winding is tapped w/ 30 terminals to provided various secondary voltage in 1 or 2 v steps

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

43 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0