## NSN 5950-00-868-3134

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-868-3134

## **Reliability Indicator:** Not established **Overall Length:** 14.250 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 13.250 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 7.000 inches single mounting facility single center group Mounting Hole Diameter: 0.310 inches single group **Frequency Rating:** 47.0 hertz single component and 63.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component **Transformer Winding Connection Type:** Delta-wve Winding Shielding Method: Internal shield brought out to terminal single component **Body Length:** 12.250 inches **Body Width:** 9.500 inches **Body Height:** 5.000 inches Maximum Operating Temp: 85.0 degrees celsius Inclosure Type: Fully enclosed **Mounting Facility Quantity:** 6 single group **Mounting Method:** Flange single group and unthreaded hole single group Winding Function And Quantity: 1 primary single component and 2 secondary single component Winding Operating Current: 8.20 amperes ac single component 1st secondary Winding Operating Voltage: 600.00 ac volts single component single primary **Terminal Type And Quantity:** 13 turret and 6 standoff, solder lug Shelf Life: N/a

## NSN 5950-00-868-3134

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

