

View Online at <https://aerobasegroup.com/nsn/5950-00-869-6630>

**Reliability Indicator:**

Not established

**Inductance Rating:**

1.00 microhenries single component single winding

**Coil Form Type:**

Hollow single component

**Core Construction:**

Powdered single component

**Adjustment Device Drive Type:**

Hex nut single component

**Body Length:**

0.516 inches

**Body Width:**

0.375 inches

**Body Height:**

0.375 inches

**Maximum Operating Temp:**

95.0 degrees celsius

**Distance Between Mounting Facility Centers:**

0.141 inches single mounting facility single center group

**End Application:**

Wsd: helicopters, sof/hh-53h pave low; green giant h-3; aircrafts, airlifter c-17a; stratolifter c-135; starlifter c-141; t-2; stratofortress b-52; f-111; galaxy c-5

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded hole single group

**Rating Method:**

Electrical single component single winding

**Thready Qty Per Inch (tpi):**

80 single group

**Thread Size:**

0.060 inches single group

**Winding Operating Current:**

10.0 milliamperes dc single component single winding

**Dc Resistance Rating In Ohms:**

10.000 single component single winding

**Quality Factor:**

52 single component single winding

**Criticality Code Justification:**

Feat

**Adjustment Method And Quantity:**

1 adjustable core single component

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Unf single group

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0