

View Online at <https://aerobasegroup.com/nsn/5950-00-869-6630>

Reliability Indicator:

Not established

Inductance Rating:

1.00 microhenries single component single winding

Coil Form Type:

Hollow single component

Core Construction:

Powdered single component

Adjustment Device Drive Type:

Hex nut single component

Body Length:

0.516 inches

Body Width:

0.375 inches

Body Height:

0.375 inches

Maximum Operating Temp:

95.0 degrees celsius

Distance Between Mounting Facility Centers:

0.141 inches single mounting facility single center group

End Application:

Wsd: helicopters, sof/hh-53h pave low; green giant h-3; aircrafts, airlifter c-17a; stratolifter c-135; starlifter c-141; t-2; stratofortress b-52; f-111; galaxy c-5

Inclosure Type:

Open

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single winding

Thready Qty Per Inch (tpi):

80 single group

Thread Size:

0.060 inches single group

Winding Operating Current:

10.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

10.000 single component single winding

Quality Factor:

52 single component single winding

Criticality Code Justification:

Feat

Adjustment Method And Quantity:

1 adjustable core single component

Special Features:

Weapon system essential

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0