

View Online at <https://aerobasegroup.com/nsn/5950-00-869-6651>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.360 inches single mounting facility single center group and 2.390 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.673 inches single mounting facility single center group and 1.703 inches single mounting facility single center group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Wye-delta

Winding Shielding Method:

Internal shield grounded to core and mounting single component

Body Length:

4.250 inches

Body Width:

2.500 inches

Body Height:

3.500 inches

Maximum Operating Temp:

170.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

600.0 milliamperes dc single component 1st secondary

Winding Operating Voltage:

35.50 ac volts single component 4th secondary

Special Features:

One primary winding; five secondary windings

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

22 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0