

View Online at <https://aerobasegroup.com/nsn/5950-00-874-4109>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.125 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.938 inches

Body Width:

2.813 inches

Body Height:

3.938 inches

Maximum Operating Temp:

125.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

4.3 amperes ac single component 1st secondary

Winding Power Rating:

85.0 volts-amperes single component 2nd secondary

Winding Operating Voltage:

8.80 ac volts single component 3rd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0