NSN 5950-00-876-4081

Saturable Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-876-4081

Reliability Indicator:

Not established

Overall Length:

6.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Overall Height:

2.125 inches

Frequency Rating:

400.0 hertz single component

Winding Shielding Method:

Internally shielded single component

Body Width:

6.000 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Clinch nut single group

Winding Function And Quantity:

1 control single component

Saturation Current Rating:

50.0 microamperes

Dc Resistance Rating In Ohms:

138.000 single component single control

Special Features:

Item has one fixed autotransformer type winding; 240 volts ac input; 5.7 ohms dc resistance on input and output

Test Data Document:

18876-9176113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

7 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A058b0