NSN 5950-00-876-4081

Saturable Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-876-4081 **Reliability Indicator:** Not established **Overall Length:** 6.250 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 5.750 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 3.000 inches single mounting facility single center group **Overall Height:** 2.125 inches Frequency Rating: 400.0 hertz single component Winding Shielding Method: Internally shielded single component **Body Width:** 6.000 inches **Inclosure Type:** Fully enclosed **Mounting Method:** Clinch nut single group **Winding Function And Quantity:** 1 control single component **Saturation Current Rating:** 50.0 microamperes Dc Resistance Rating In Ohms: 138.000 single component single control **Special Features:** Item has one fixed autotransformer type winding; 240 volts ac input; 5.7 ohms dc resistance on input and output **Test Data Document:** 18876-9176113 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 7 turret Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A058b0