NSN 5950-00-879-4244

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-879-4244

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.687 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.437 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

64.00 millihenries single component 2nd winding

Frequency Rating:

800.0 hertz single component

Body Length:

2.310 inches

Body Width:

2.060 inches

Body Height:

3.120 inches

Winding Quantity:

2 single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

3.2 amperes dc single component 1st winding

Dc Resistance Rating In Ohms:

2.600 single component 2nd winding

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 solder stud

Reference Number Differentiating Characteristics:

As differentiated by navord od41152

Shelf Life:

N/a

NSN 5950-00-879-4244

Reactor - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0