## NSN 5950-00-879-9518

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-879-9518

| Reliability Indicator:  |
|---|
| Not established   |
| Overall Length:   |
| 11.000 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 6.730 inches single mounting facility single center group and 6.770 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 4.980 inches single mounting facility single center group and 5.020 inches single mounting facility single center group |
| Mounting Slot Width:  |
| 0.276 inches single group and 0.286 inches single group   |
| Frequency Rating:   |
| 60.0 hertz single component   |
| Input-output Phase Relationship:  |
| Single phase to single phase single component   |
| Winding Shielding Method:   |
| Internal shield grounded to inclosure single component  |
| Body Length:  |
| 9.940 inches  |
| Body Width:   |
| 6.000 inches  |
| Body Height:  |
| 7.500 inches  |
| Maximum Operating Temp:   |
| 130.0 degrees celsius   |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 6 single group  |
| Mounting Method:  |
| Flange single group and slot single group   |
| Winding Function And Quantity:  |
| 1 primary single component and 1 secondary single component   |
| Winding Power Rating:   |
| 1.5 volts-amperes single component single secondary   |
| Winding Operating Voltage:  |
| 115.00 ac volts single component single secondary   |
| Terminal Type And Quantity:   |
| 6 threaded stud   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5950-00-879-9518

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0