NSN 5950-00-880-8334

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-880-8334

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| Between 2.959 inches and 3.041 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.615 inches single mounting facility single center group and 2.635 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.295 inches single mounting facility single center group and 1.305 inches single mounting facility single center group |
| Overall Height: |
| 1.668 inches |
| Overall Width: |
| 1.953 inches |
| Frequency Rating: |
| 1.35 kilohertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Operating Temp: |
| 170.0 degrees celsius |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thread Size: |
| 0.112 inches single group |
| Winding Operating Current: |
| 325.0 milliamperes ac single component single primary |
| Winding Operating Voltage: |
| 320.00 ac volts single component 1st secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-00-880-8334

Power Transformer - Page 2 of 2



Fiig:

A058b0