

View Online at <https://aerobasegroup.com/nsn/5950-00-881-6436>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Mounting Slot Width:

0.188 inches single group

Frequency Rating:

47.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta

Body Length:

4.380 inches

Body Width:

2.120 inches

Body Height:

3.880 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

110.0 milliamperes dc single component single secondary

Winding Operating Voltage:

343.00 ac volts single component single secondary and 456.00 ac volts single component single secondary

Special Features:

Secondary current rated as dc

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0