NSN 5950-00-882-7271

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-882-7271

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.437 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.937 inches

Body Width:

3.375 inches

Body Height:

5.250 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.190 inches single group

Winding Operating Current:

500.0 milliamperes ac single component single secondary and 4.0 amperes ac single component single secondary and 3.5 amperes ac single component single secondary and 1.4 amperes ac single component single secondary and 1.4 amperes ac single component single secondary and 1.0 amperes ac single component single secondary and 80.0 milliamperes ac single component single secondary

Winding Operating Voltage:

24.00 ac volts single component single secondary and 50.00 ac volts single component single secondary and 65.00 ac volts single component single secondary and 175.00 ac volts single component single secondary and 175.00 ac volts single component single secondary and 250.00 ac volts single component single secondary action secondary ac

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

Domilitorization

NSN 5950-00-882-7271

Power Transformer - Page 2 of 2

Fiig: A058b0

