

View Online at <https://aerobasegroup.com/nsn/5950-00-883-7725>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

6.00 henry single component single winding

Body Length:

2.830 inches

Body Width:

2.475 inches

Body Height:

2.359 inches

End Application:

Spruance class d (963), virginia class cgn(41) , nimitz class cvn, forrestal class cv

Winding Quantity:

1 single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.164 inches single group

Winding Operating Current:

125.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

240.000 single component single winding

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0