NSN 5950-00-884-0448

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-884-0448

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.062 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.312 inches single mounting facility single center group |
| Frequency Rating: |
| 50.0 hertz single component and 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.062 inches |
| Body Width: |
| 2.625 inches |
| Body Height: |
| 4.250 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Voltage: |
| 12.50 ac volts single component all secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 1 connector, receptacle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| <u></u> |
| Demilitarization: |
| No |
| |

Fiig:

A058b0