

View Online at <https://aerobasegroup.com/nsn/5950-00-884-1005>

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

3.250 inches

Body Width:

2.750 inches

Body Height:

4.250 inches

Inclosure Type:

Partially enclosed, half shell

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 6 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

1.0 amperes ac single component 4th secondary

Winding Operating Voltage:

6.30 ac pounds per hour wet single component 4th secondary

Special Features:

6.3 v center tapped 0.3 amp fifthsecondary, 27 v center tapped 0.450 amp sixth secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

18 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0