## NSN 5950-00-889-9863

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-889-9863

| Reliability Indicator:   |
|--|
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:  |
| 4.625 inches single mounting facility single center group  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:   |
| 3.000 inches single mounting facility single center group  |
| Frequency Rating:  |
| 47.0 hertz single component and 63.0 hertz single component  |
| Input-output Phase Relationship:   |
| Single phase to single phase single component  |
| Winding Shielding Method:  |
| Internal shield grounded to inclosure single component   |
| Body Length:   |
| 6.500 inches   |
| Body Width:  |
| 4.500 inches   |
| Body Height:   |
| 5.375 inches   |
| Inclosure Type:  |
| Open   |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Threaded hole single group   |
| Winding Function And Quantity:   |
| 1 primary single component and 3 secondary single component  |
| Thready Qty Per Inch (tpi):  |
| 32 single group  |
| Thread Size:   |
| 0.190 inches single group  |
| Winding Operating Current:   |
| 20.0 milliamperes ac single component 1st secondary  |
| Winding Operating Voltage:   |
| 110.00 ac volts single component single primary and 115.00 ac volts single component single primary and 130.00 ac volts single |
| component single primary   |
| Thread Series Designator:  |
| Unf single group   |
| Terminal Type And Quantity:  |
| 13 terminal block w/screws   |
| Shelf Life:  |

--

N/a

**Unit Of Measure:** 

## NSN 5950-00-889-9863

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0