

View Online at <https://aerobasegroup.com/nsn/5950-00-890-2982>

Reliability Indicator:

Not established

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.375 inches

Body Width:

1.625 inches

Body Height:

1.625 inches

Distance Between Mounting Facility Centers:

1.031 inches single mounting facility single center group

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Thread Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

8.0 milliamperes ac single component 3rd secondary

Winding Operating Voltage:

8.20 ac volts single component 1st secondary and 30.60 ac volts single component 1st secondary and 38.80 ac volts single component 1st secondary

Special Test Features:

Navord od41152

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

11 standoff, solder lug

Reference Number Differentiating Characteristics:

As differentiated by special test features

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0