# NSN 5950-00-891-2543

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-891-2543

## Reliability Indicator:

Not established

## **Overall Length:**

Between 3.810 inches and 4.000 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

3.090 inches single mounting facility single center group and 3.290 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

**Overall Height:** 

1.960 inches

**Overall Width:** 

Between 2.870 inches and 3.370 inches

#### Mounting Slot Width:

0.170 inches single group

#### Frequency Rating:

400.0 hertz single component

# Input-output Phase Relationship:

Single phase to single phase single component

## Winding Shielding Method:

Internal shield brought out to terminal single component

#### Inclosure Type:

Fully enclosed

# Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

# Winding Function And Quantity:

1 primary single component and 3 secondary single component

# Winding Operating Voltage:

40.00 ac volts single component single primary

# Test Data Document:

97151-8810307 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Terminal Type And Quantity:

11 wire lead

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A058b0