

View Online at <https://aerobasegroup.com/nsn/5950-00-892-8149>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 800.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

4.500 inches

Body Width:

3.750 inches

Body Height:

3.125 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 8 secondary single component

Features Provided:

Tinned wire leads and color coded lead

Thread Size:

0.190 inches single group

Winding Operating Current:

600.0 milliamperes ac single component 4th secondary

Winding Operating Voltage:

6.30 ac volts single component 4th secondary

Special Features:

2 primary windings, 8 secondaries

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

6 wire lead and 19 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0