NSN 5950-00-895-6412

Current Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-895-6412

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.560 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.188 inches single group |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Three phase to three phase single component |
| Body Length: |
| 5.440 inches |
| Body Width: |
| 2.030 inches |
| Body Height: |
| 3.000 inches |
| Installation For Which Designed: |
| Indoor nonportable |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 1st group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 secondary single component |
| Winding Operating Current: |
| 222.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 3.33 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 4 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A058b0