## NSN 5950-00-897-8098

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-897-8098

### Reliability Indicator:

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

#### Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

#### **Transformer Winding Connection Type:**

Wye-wye

#### **Winding Shielding Method:**

Internal shield grounded to core single component

### **Body Length:**

3.625 inches

### **Body Width:**

1.875 inches

### **Body Height:**

2.340 inches

### **Maximum Operating Temp:**

140.0 degrees celsius

### Inclosure Type:

Fully enclosed

### **Mounting Facility Quantity:**

4 single group

### **Mounting Method:**

Threaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 4 secondary single component

### Thready Qty Per Inch (tpi):

32 single group

### **Thread Size:**

0.138 inches single group

### **Winding Operating Current:**

40.00 milliamperes ac single component 1st secondary

### **Winding Operating Voltage:**

35.00 ac volts single component 2nd secondary and 115.00 ac volts single component 2nd secondary

### **Thread Series Designator:**

Unc single group

### **Terminal Type And Quantity:**

21 solder stud

# NSN 5950-00-897-8098

Power Transformer - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0