

View Online at <https://aerobasegroup.com/nsn/5950-00-898-1345>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.296 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.859 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

3.062 inches

Body Width:

2.625 inches

Body Height:

4.500 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

6.0 amperes dc single component all secondary and 12.0 amperes dc single component all secondary

Winding Operating Voltage:

8.25 ac volts single component all secondary and 20.25 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0