## NSN 5950-00-898-1345

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-898-1345

| View Online at https://aerobasegroup.com/nsn/5950-00-898-1345                                    |
|--|
| Reliability Indicator:   |
| Not established  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:                        |
| 2.296 inches single mounting facility single center group  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:                         |
| 1.859 inches single mounting facility single center group  |
| Frequency Rating:  |
| 50.0 hertz single component or 60.0 hertz single component                                       |
| Input-output Phase Relationship:   |
| Single phase to single phase single component  |
| Winding Shielding Method:  |
| Internal shield grounded to core single component  |
| Body Length:   |
| 3.062 inches   |
| Body Width:  |
| 2.625 inches   |
| Body Height:   |
| 4.500 inches   |
| Inclosure Type:  |
| Hermetically sealed  |
| Mounting Facility Quantity:  |
| 4 single group   |
| Mounting Method:   |
| Threaded stud single group   |
| Winding Function And Quantity:   |
| 2 primary single component and 2 secondary single component                                      |
| Thread Size:   |
| 0.164 inches single group  |
| Winding Operating Current:   |
| 6.0 amperes dc single component all secondary and 12.0 amperes dc single component all secondary |
| Winding Operating Voltage:   |
| 8.25 ac volts single component all secondary and 20.25 ac volts single component all secondary   |
| Thread Series Designator:  |
| Unc single group   |
| Terminal Type And Quantity:  |
| 10 tab, solder lug   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| - <del>-</del>   |
| Demilitarization:  |

No

## NSN 5950-00-898-1345

Power Transformer - Page 2 of 2



Fiig:

A058b0