## NSN 5950-00-898-9015

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-898-9015

Note established  Mounting Hole Diameter: 0.156 inches single group Inductance Type: Fixed  Inductance Rating: 38.40 millihenries single component single winding and 68.60 millihenries single component single winding Body Length: 1.512 inches Body Width: 1.312 inches Body Height: 0.750 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms: 8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity: 3 tab, solder lug
Inductance Type: Fixed Inductance Rating: 38.40 millihenries single component single winding and 68.60 millihenries single component single winding Body Length: 1.512 inches Body Width: 1.312 inches Body Height: 0.750 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms: 8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
Inductance Type: Fixed Inductance Rating: 38.40 millihenries single component single winding and 68.60 millihenries single component single winding Body Length: 1.512 inches Body Width: 1.312 inches Body Height: 0.750 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms: 8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
Fixed Inductance Rating:  38.40 millihenries single component single winding and 68.60 millihenries single component single winding Body Length:  1.512 inches Body Width:  1.312 inches Body Height:  0.750 inches Winding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms:  8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
Inductance Rating:  38.40 millihenries single component single winding and 68.60 millihenries single component single winding Body Length:  1.512 inches Body Width:  1.312 inches Body Height:  0.750 inches Winding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms:  8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
Body Length: 1.512 inches Body Width: 1.312 inches Body Height: 0.750 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms: 8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
Body Length:  1.512 inches Body Width:  1.312 inches Body Height:  0.750 inches Winding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms:  8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
1.512 inches  Body Width: 1.312 inches  Body Height: 0.750 inches  Winding Quantity: 1 single component Inclosure Type: Fully enclosed  Mounting Facility Quantity: 2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Dc Resistance Rating In Ohms: 8.100 single component single winding  Special Features: Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
Body Width:  1.312 inches  Body Height:  0.750 inches  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  2 single group  Mounting Method:  Flange single group and unthreaded hole single group  Rating Method:  Electrical single component single winding  Dc Resistance Rating In Ohms:  8.100 single component single winding  Special Features:  Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
1.312 inches  Body Height: 0.750 inches  Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms: 8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
Body Height:  0.750 inches  Winding Quantity:  1 single component  Inclosure Type: Fully enclosed  Mounting Facility Quantity:  2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method:  Electrical single component single winding  Dc Resistance Rating In Ohms:  8.100 single component single winding  Special Features:  Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
O.750 inches  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  2 single group  Mounting Method:  Flange single group and unthreaded hole single group  Rating Method:  Electrical single component single winding  Dc Resistance Rating In Ohms:  8.100 single component single winding  Special Features:  Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  2 single group  Mounting Method:  Flange single group and unthreaded hole single group  Rating Method:  Electrical single component single winding  Dc Resistance Rating In Ohms:  8.100 single component single winding  Special Features:  Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms: 8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
Inclosure Type: Fully enclosed Mounting Facility Quantity: 2 single group Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms: 8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
Fully enclosed  Mounting Facility Quantity:  2 single group  Mounting Method:  Flange single group and unthreaded hole single group  Rating Method:  Electrical single component single winding  Dc Resistance Rating In Ohms:  8.100 single component single winding  Special Features:  Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
Mounting Facility Quantity:  2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Dc Resistance Rating In Ohms: 8.100 single component single winding  Special Features: Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Dc Resistance Rating In Ohms: 8.100 single component single winding  Special Features: Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
Mounting Method: Flange single group and unthreaded hole single group Rating Method: Electrical single component single winding Dc Resistance Rating In Ohms: 8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
Flange single group and unthreaded hole single group  Rating Method:  Electrical single component single winding  Dc Resistance Rating In Ohms:  8.100 single component single winding  Special Features:  Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
Rating Method:  Electrical single component single winding  Dc Resistance Rating In Ohms:  8.100 single component single winding  Special Features:  Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
Electrical single component single winding  Dc Resistance Rating In Ohms:  8.100 single component single winding  Special Features:  Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
Dc Resistance Rating In Ohms: 8.100 single component single winding Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
8.100 single component single winding  Special Features:  Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
Special Features: Single winding tapped at 5.9 ohms Terminal Type And Quantity:
Single winding tapped at 5.9 ohms  Terminal Type And Quantity:
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A058b0