

View Online at <https://aerobasegroup.com/nsn/5950-00-900-4839>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility single center group

Mounting Hole Diameter:

0.193 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.620 inches

Body Width:

3.082 inches

Body Height:

3.305 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

9.0 milliamperes ac single component single secondary

Winding Operating Voltage:

5.00 ac volts single component single secondary and 12.50 ac volts single component single secondary and 16.25 ac volts single component single secondary and 18.50 ac volts single component single secondary and 21.50 ac volts single component single secondary and 23.75 ac volts single component single secondary and 27.50 ac volts single component single secondary and 35.00 ac volts single component single secondary and 40.00 ac volts single component single secondary

Special Features:

Max phase shift from primary to secondary is porm 6 sec

Terminal Type And Quantity:

13 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0