

View Online at <https://aerobasegroup.com/nsn/5950-00-900-5773>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.188 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.188 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

1.625 inches

**Body Width:**

1.625 inches

**Body Height:**

2.375 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary, variable autotransformer type single component

**Thread Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

25.0 milliamperes ac single component single primary input

**Winding Operating Voltage:**

3.71 ac kilovolts single component single primary output and 7.43 ac kilovolts single component single primary output and 11.14 ac kilovolts single component single primary output and 14.85 ac kilovolts single component single primary output and 18.57 ac kilovolts single component single primary output and 22.28 ac kilovolts single component single primary output and 29.71 ac kilovolts single component single primary output and 37.14 ac kilovolts single component single primary output and 74.28 ac kilovolts single component single primary output and 148.50 ac kilovolts single component single primary output and 18.57 ac volts single component single primary output and 22.28 ac volts single component single primary output

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

16 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

**Fig:**

A058b0