

View Online at <https://aerobasegroup.com/nsn/5950-00-900-5773>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.188 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.188 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

1.625 inches

Body Width:

1.625 inches

Body Height:

2.375 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary, variable autotransformer type single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

25.0 milliamperes ac single component single primary input

Winding Operating Voltage:

3.71 ac kilovolts single component single primary output and 7.43 ac kilovolts single component single primary output and 11.14 ac kilovolts single component single primary output and 14.85 ac kilovolts single component single primary output and 18.57 ac kilovolts single component single primary output and 22.28 ac kilovolts single component single primary output and 29.71 ac kilovolts single component single primary output and 37.14 ac kilovolts single component single primary output and 74.28 ac kilovolts single component single primary output and 148.50 ac kilovolts single component single primary output and 18.57 ac volts single component single primary output and 22.28 ac volts single component single primary output

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

16 wire hook

Shelf Life:

N/a

Unit Of Measure:

Fiig:

A058b0