NSN 5950-00-901-9944

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-901-9944

| New Online at https://defobasegroup.com/hsin/3300-00-301-3344 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.438 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.688 inches single mounting facility single center group |
| Frequency Rating: |
| 50.0 hertz single component or 60.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.313 inches |
| Body Width: |
| 2.063 inches |
| Body Height: |
| 2.500 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 2.0 amperes ac single component single secondary |
| Winding Operating Voltage: |
| 6.30 ac volts single component single secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5950-00-901-9944

Power Transformer - Page 2 of 2

Fiig: A058b0

