## NSN 5950-00-902-6448

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-902-6448
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.062 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.250 inches single mounting facility single center group
Frequency Rating:
400.0 hertz single component
Input-output Phase Relationship:
Three phase to three phase single component
Body Length:
3.060 inches
Body Width:
2.750 inches
Body Height:
1.750 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
770.0 milliamperes ac single component single secondary
Winding Operating Voltage:
83.00 ac volts single component single secondary
Test Data Document:
10001-226639 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
6 solder stud
Shelf Life:
N/a
Unit Of Measure:

\_\_

## NSN 5950-00-902-6448

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0