# NSN 5950-00-902-6448

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-902-6448

## Reliability Indicator:

Not established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.062 inches single mounting facility single center group

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

#### **Frequency Rating:**

400.0 hertz single component

#### Input-output Phase Relationship:

Three phase to three phase single component

Body Length:

3.060 inches

Body Width:

2.750 inches

Body Height:

1.750 inches

Inclosure Type:

Fully enclosed

**Mounting Facility Quantity:** 

4 single group

Mounting Method:

Threaded hole single group

#### Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### Thready Qty Per Inch (tpi):

32 single group

**Thread Size:** 

0.138 inches single group

#### Winding Operating Current:

770.0 milliamperes ac single component single secondary

#### Winding Operating Voltage:

83.00 ac volts single component single secondary

#### **Test Data Document:**

10001-226639 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Thread Series Designator:

Unc single group

**Terminal Type And Quantity:** 

6 solder stud

#### Shelf Life:

N/a

### Unit Of Measure:

# NSN 5950-00-902-6448

Power Transformer - Page 2 of 2

Demilitarization:

No

Fiig:

A058b0

