

View Online at <https://aerobasegroup.com/nsn/5950-00-903-5872>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.375 inches single mounting facility single center group

Mounting Slot Width:

0.312 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

1.0 kilovolt-ampere single component

Body Length:

6.250 inches

Body Width:

5.250 inches

Body Height:

4.500 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and slot single group

Winding Function And Quantity:

2 primary single component and 1 secondary single component

Winding Operating Current:

8.7 amperes ac single component single secondary

Winding Operating Voltage:

110.00 ac pounds per hour dry single component single secondary and 120.00 ac pounds per hour with retaining chain single component single secondary 220.00 ac pounds per hour dry single component all primary and 240.00 ac pounds per hour with retaining chain single component all primary

Terminal Type And Quantity:

6 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0