

View Online at <https://aerobasegroup.com/nsn/5950-00-904-1553>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.250 inches single mounting facility single center group

Overall Height:

8.630 inches

Frequency Rating:

57.0 hertz single component and 63.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

6.000 inches

Body Width:

5.000 inches

Body Height:

7.000 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 9 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

700.0 milliamperes dc single component 4th secondary

Winding Power Rating:

31.2 volts-amperes single component 4th secondary

Winding Operating Voltage:

44.50 ac volts single component 3rd secondary

Special Features:

One primary and nine secondaries

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

24 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0