## NSN 5950-00-904-4943

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-904-4943
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.450 inches single mounting facility single center group and 1.550 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.980 inches single mounting facility single center group and 1.020 inches single mounting facility single center group
Mounting Slot Width:
0.156 inches single group and 0.164 inches single group
Inductance Type:
Fixed
Inductance Rating:
500.00 millihenries single component single winding
Frequency Rating:
2.28 kilohertz single component and 2.52 kilohertz single component
Body Length:
2.000 inches
Body Width:
2.200 inches
Body Height:
1.900 inches
Winding Quantity:
1 single component
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
Mounting Method:
Flange single group and slot single group
Rating Method:
Electrical single component single winding
Winding Conductor Size:
0.05707 inches american wire gage single component single winding
Winding Operating Current:
350.0 milliamperes dc single component single winding
Dc Resistance Rating In Ohms:
76.000 single component single winding
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a

\_\_

**Unit Of Measure:** 

## NSN 5950-00-904-4943

Reactor - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A058b0