## NSN 5950-00-904-4962

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-904-4962

## **Reliability Indicator:** Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 2.520 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.020 inches single mounting facility single center group **Mounting Slot Width:** 0.316 inches single group **Frequency Rating:** 380.0 hertz single component and 420.0 hertz single component Input-output Phase Relationship: Three phase to three phase single component **Transformer Winding Connection Type:** Delta-delta Winding Shielding Method: Internal shield grounded to core single component **Body Length:** 5.500 inches **Body Width:** 3.000 inches **Body Height:** 4.500 inches Inclosure Type: Fully enclosed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Flange single group and slot single group Winding Function And Quantity: 1 primary single component and 1 secondary single component Winding Operating Current: 2.61 amperes ac single component single secondary Winding Operating Voltage: 230.00 ac pounds per hour wet single component single secondary **Terminal Type And Quantity:** 6 tab, solder lug Shelf Life: N/a Unit Of Measure: ---

## **Demilitarization:**

No

## NSN 5950-00-904-4962

Power Transformer - Page 2 of 2

**Fiig:** A058b0

