NSN 5950-00-904-7374

Power Transformer - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5950-00-904-7374 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.000 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.156 inches single group |
| Frequency Rating: |
| 380.0 hertz single component and 420.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 2.380 inches |
| Body Outside Diameter: |
| 2.120 inches |
| Body Height: |
| 2.250 inches |
| Maximum Operating Temp: |
| 65.0 degrees celsius |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Winding Operating Current: |
| 35.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 12.80 ac volts single component single secondary |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

No

Fiig: A058b0