NSN 5950-00-905-8835

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-905-8835

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.062 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.312 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

5.062 inches

Body Width:

4.312 inches

Body Height:

5.500 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.250 inches single group

Winding Operating Current:

250.0 milliamperes ac single component single secondary

Winding Operating Voltage:

1.60 ac kilovolts single component single secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

NSN 5950-00-905-8835

Power Transformer - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A058b0